

**AUTOMATIC COOKING FIRE SUPPRESSION**

# StoveTop FireStop® MICROHOOD SPECIFICATION

<b>INTENDED USE</b>	Indoor, residential stove top pan fires (not recommended for deep fat fryers)
<b>ACTIVATION METHOD</b>	Automatic when there is direct, sustained contact with a flame
<b>POWDER DISPERSAL METHOD</b>	Gravity (non-pressurised)
<b>PRIMARY SUPPRESSION AGENT</b>	Non-Toxic dry powder
<b>INTENDED APPLICATION</b>	Microwave oven overhead, cabinets, or other lower vent hoods
<b>REQUIRED VERTICAL CLEARANCE</b>	15-27" (38-68cm) between the underside of the cabinet/microwave and the cooking surface
<b>REQUIRED HORIZONTAL DISTANCE FROM BACK WALL</b>	Should be at least 14" (36cm) from back wall (or back of stove)
<b>WEIGHT - TOTAL PRODUCT</b>	Approximately 30 oz. (850g) - per housing
<b>WEIGHT - POWDER</b>	Approximately 5.2 oz. (147g) -per canister / Each pair contains four canisters
<b>HEIGHT</b>	2.2" (5.6cm)
<b>LENGTH</b>	13.9" (35cm) - including mounting bracket
<b>WIDTH</b>	3.9" (9.9cm)
<b>INSTALLATION METHOD</b>	Drywall anchors and screws (included) hold device to back wall (extension bars available)
<b>NUMBER OF DEVICES NEEDED TO COVER A 4-BURNER STOVE TOP</b>	Two (sold as a pair)
<b>TESTS PERFORMED</b>	Device and dry powder tested by an independent nationally recognised testing laboratory (NRTL)
<b>EFFECTIVE LIFE</b>	6 years, replace upon activation or before 'remove or replace before' date found on label.

