

AUTOMATIC COOKING FIRE SUPPRESSION

StoveTop FireStop® RANGEHOOD SPECIFICATION

INTENDED USE	Indoor, residential stove top pan fires (not recommended for deep fat fryers)
ACTIVATION METHOD	Automatic when there is direct, sustained contact with a flame
POWDER DISPERSAL METHOD	Gravity (non-pressurised)
PRIMARY SUPPRESSION AGENT	Non-Toxic dry powder
INTENDED APPLICATION	Traditional range hoods
REQUIRED VERTICAL CLEARANCE	27-35" (68-88cm) between the burner and the bottom of the surface where the magnet will attach
REQUIRED HORIZONTAL DISTANCE FROM BACK WALL	Position each canister at the midpoint between the center of the front and back burners on each side
WEIGHT - TOTAL PRODUCT	Approximately 12 oz. (340g)
WEIGHT - POWDER	Approximately 9 oz. (255g) -per canister
HEIGHT	3.5" (9cm) - including magnet assembly
LENGTH	3.4" (8.6cm) - diameter
WIDTH	3.4" (8.6cm) - diameter
INSTALLATION METHOD	Industrial strength magnet holds device to range hood. Alternative mounting kits available
NUMBER OF DEVICES NEEDED TO COVER A 4-BURNER STOVE TOP	Two (sold as a pair)
TESTS PERFORMED	Device and dry powder tested by an independent nationally recognised testing laboratory (NRTL)
EFFECTIVE LIFE	6 years, replace upon activation or before 'remove or replace before' date found on label.

