

The EUW-MA-05 is the latest in wireless multi-criteria detector technology. It is a fully intelligent device and compatible with all Euro-fi wireless Translator and Expander modules.

The detector is designed for open area protection and combines both dual-path smoke and heat detection technologies for improved performance, whilst maintaining the high levels of unwanted alarm rejection. Utilising well-proven adaptive radio signal processing algorithms ensures that the highest levels of life safety and system reliability are achieved. An in-built magnet test allows easy activation to verify correct functionality and response.

Key Features

Technical Specification

- Advanced dual-path optical chamber design
- · Internal algorithm processing optimises performance
- 3rd party approved
- Up to 10 year battery life
- · Utilises standard low-cost lithium battery technology
- Multiple smoke and heat sensitivity settings
- Bi-directional wireless communications
- Compatible with all Euro-fi translator and expanders
- Complies with the latest multi-sensor standard EN54-29
- 5 year product warranty

Max radiated power

Dimensions

Batteries

Weight

IP rating Magnet test

Operating frequency range

Operating frequency channels

Choice of sensitivity settings

Temperature range (no icing)

Standards & Approvals

BS EN 54-7: Smoke detectors

868 - 870 MHz

Multiple

150g

Yes

95% RH 40

14 dBm (25mW)

3 smoke / 2 heat

110mm x 70mm

-10°C to +55°C*

2 x CR123A

CEA4012

BS EN 54-5

BS EN 54-25: Components using radio links

Class P: Heat detectors

BS EN54-29: *Multi-sensor fire detectors*



Ø 110 mm



** Performance may vary at extremes of range

Max tolerated humidity (non condensing)

Eurotech Fire Systems Ltd

Tel: +44 (0) 203 141 0999 Web: ww.eurotechfire.com Head office: 19/20 Stratfield Park, Elettra Avenue, Hampshire, PO7 7XN Regional offices: Scotland, North Midlands, London