

The EUW-TA-05 is the latest in wireless heat detector technology. It is a fully intelligent device and compatible with all Euro-fi wireless Translator and Expander modules. The detector is designed for open area protection giving the best possible warning of a fire condition in locations where smoke detection technology is not suitable.

The well-proven adaptive radio signal processing algorithms ensure the highest levels of life safety and system reliability are achieved. An in-built magnet test allows easy activation to verify correct functionality and response.

Key Features

- Twin alarm LEDs for 360 degree visibility
- · Internal algorithm processing optimises performance
- 3rd party approved
- Up to 10 year battery life
- Utilises standard low-cost lithium battery technology
- Bi-directional wireless communication
- Compatible with all Euro-fi translators and expanders
- Multiple sensitivity settings
- 5 year product warranty
- Device identification tab

Standards & Approvals

BS EN 54-5 Class P: Heat detectors, point detectors

BS EN 54-25:

Components using radio links and system requirements



Operating frequency range	868 - 870 MHz	(ac)
Max radiated power	14 dBm (25mW)	(a)
Operating frequency channels	Multiple	
Class A1R	(58°C max) or	
Class BS high temperature	(78°C)	
Dimensions	110mm x 70mm	CS C
Batteries	2 x CR123A	
Weight	190g	Ø 110 mm
Temperature range (no icing)	-10°C to +55°C**	
Max tolerated humidity (non condensing)	95% RH	
IP rating	40	
erformance may vary at extremes of range		

Eurotech Fire Systems Ltd

Tel: +44 (0) 203 141 0999 Web: ww.eurotechfire.com Head office: 19/20 Stratfield Park, Elettra Avenue, Hampshire, PO7 7XN Regional offices: Scotland, North Midlands, London